

Media Tube Lite RGBW 1000 5PXL

Media Tube Lite RGBW | Media luminaires



Areas of application

- Various mounting options
- Accent lighting
- Dynamic facade lighting with long light ribbons
- Low resolution media facades
- Stadiums, bridges, hotels, office buildings


Product benefits

- Easy to integrate into various facade claddings thanks to slim profile
- Seamless integration into e:cue systems
- High efficacy
- High brightness at low power consumption

Product features

- RGB and True White LED in one system
- Width: 15.4 mm
- Mounting bracket with adjustable 0...90° mounting angle
- Control via DMX

IP 66



Product datasheet

Technical data

Electrical data

Nominal wattage	16 W
Connected load	16 W
Nominal voltage	24.0 V
Supply voltage	24 V

Light technical data

Beam angle	110 °
------------	-------

Dimensions & weight

Length	1000 mm
Width	16.0 mm
Height	18.0 mm
Product weight	0.4 kg

Colors & materials

Body material	aluminium
Product color	silver

Additional product data

Number of lighting outlets	60
----------------------------	----

Certificates & standards

Type of protection	IP65
--------------------	------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4055462124548	Media Tube Lite RGBW 1000 5PXL	Unpacked 1	- x - x -		
4055462124555	Media Tube Lite RGBW 1000 5PXL	Shipping carton box 54	1034 mm x 524 mm x 198 mm	107.28 dm ³	23580.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.